

# RUPARTS

Email: [info@ruparts.eu](mailto:info@ruparts.eu)

[www.ruparts.eu](http://www.ruparts.eu)

Exhaust cover stabilizer for GasGas (Trial)

building year 2011 or newer (including all necessary parts)



Enables you to fix the final exhaust cover of your GasGas-trial-motorcycle durable and although elastic – preventative or for repair!

You can repair the final exhaust cover although if plastics which held the fast nuts inside are broken!

Never get a problem with the final exhaust cover again!

Cool design!

Assembly instruction on the backside! (2011)

## **Assembly instruction!**

Remove the dirt from the exhaust. Proof whether you can move the ring shaped part of the stabilizer on the aluminium exhaust-hose or not. It may be damaged in case of a fall. Maybe you have to file or bend it a little with a tong (the alu-exhaust-hose).

### **How to mount if the final exhaust cover is unimpaired!**

Unloose all Screws of the final exhaust cover. Remove the furthest screw and push the exhaust cover into the original position. Put the exhaust stabilizer onto the alu-exhaust-hose and move it - so you can mount the new screw (M5 x 12) and fix it. Now bore through both 4mm drill holes and mount the 4mm blind rivets.

Fix all screws – ready for race!

### **How to mount if the final exhaust cover is damaged!**

Unloose all Screws of the final exhaust cover. Push the exhaust cover into the original position. If it is not possible remove the final exhaust cover complete and remove all screw-parts which are not necessary. Now push the exhaust cover into the original position again. Put the exhaust stabilizer onto the alu-exhaust-hose and move it - so you can mount the 5mm blind rivet into the bore of the M5 screw. Now bore through both 4mm drill holes and mount the 4mm blind rivets.

Fix all other screws – ready for race!

### **How to disassembly the exhaust stabilizer for replacing the exhaust packing wool!**

Drill out the heads (only the heads) of the blind rivets. Remove the Exhaust stabilizer. Push the remaining parts with a nail punch into the exhaust. This remaining parts will be removed with the exhaust packing wool.

